Centrella[™] Smart+ Bed

Model CNT255 Skills Checklist

Staff Signature:	
Trainer's Signature:	
Date:	



COMPLETED

Perform the following.

Frame Features

Fra	rame Features		
1.	State the maximum patient weight limit.		
2.	Unplug bed's power cord . Identify the one (1) audible and two (2) visual cues when the bed is unplugged from power.		
3.	Demonstrate use of battery backup to raise head. Identify controls available on battery backup. Identify % battery 'charged' indicator for bed frame.		
4.	Lock Head control and unlock retractable foot feature and shorten the bed to shortest position. State all controls that can be locked out.		
5.	Explain how bed indicates the communication cable/call light is not connected. There are two (2) audible and two (2) visual indicators.		
6.	Lower the head and intermediate siderails on one side of the bed. Raise into a locked position.		
7.	Identify the one (1) audible and one (1) visual cue that the bed is in the lowest position .		
8.	Elevate the lower legs/foot-of-bed to be parallel to the floor. Explain when this may be useful. Slightly lower feet and then level the legs.		
9.	Using CPR control, position bed for CPR. Identify situations where a CPR board may be recommended.		
10.	Remove headboard for emergency access to the head of the bed.		
11.	Identify two (2) head-of-bed indicators on the bed.		
12.	Identify the built-in siderail line managers.		
13.	Identify the hip indicator label for patient placement in the bed. Explain why this is important.		
14.	Point to the three (3) areas for attaching restraints on one side of the bed.		
15.	Identify the foley/drainage bag holder on one side of the bed.		
16.	Explain the foley position limit. Demonstrate how to turn it on and how to recognize it is active.		
17.	Explain the difference between when the bed sounds a single beep and a triple beep.		
18.	Locate the Boost [®] control. Explain when it is used and what happens when Boost is activated.		
19.	Explain what the three (3) lighted SafeView®+ (optional) icons (at the foot-end of the bed and on the floor) indicate. Why are there blinking lights? Correct the situation to stop the lights from blinking.		
20.	Explain purpose of lighted siderail grip (optional) . What turns it on? Explain meaning when light is blue? Amber? Flashing Amber?		
21.	Locate and explain purpose of the night light. Identify what activates the brightening of the night light.		
22.	Locate these patient accessible siderail features: Siderail storage for devices, urinal holder, and head-of-bed angle indicator.		



Pe	rform the following.	COMPLETED
23.	Explain the patient remote controls: nurse call, bed exit 'on' reminder, stand assist. Hang patient remote on all three (3) siderail locations.	
24.	Demonstrate putting brake pedal into steer mode and then into neutral.	
25.	Demonstrate using the IntelliDrive [®] Powered Transport (optional) system by moving the bed forward and backward. Demonstrate how to move bed side-to-side, as if to straighten in a room or up against a stretcher. State % of battery charge.	
GC	l® Touchscreen	
26.	Define the three-levels of bed exit sensitivity.	
27.	Set the bed exit sensitivity to alert before a patient gets out of the bed. State the four (4) ways you know bed exit is ON (patient in bed).	
28.	Pre-emptively SILENCE the bed exit alert. Explain how to add time for Silence period and the meaning of triple beep.	
29.	Resume the bed exit alert . Identify two (2) ways to do this.	
30.	Explain the difference between the scale 'new patient zero' and 'same patient re-zero.'	
31.	Zero scale for 'new patient.' Identify three (3) screens you can check to see if the scale was zeroed.	
32.	Weigh patient. Demonstrate how to display weight in lbs, then save weight in kgs. Recall weight after saving.	
33.	Set the < 30° head-of-bed limit . Turn off function.	
34.	Locate the stand assist control on the GCI® Touchscreen.	
35.	Demonstrate putting the bed into the chair position. Explain meaning of triple beep.	
36.	Level the bed from the chair position using the bed flat control.	
37.	Locate the settings screen. Turn OFF the SafeView [®] alert lights.	
38.	Turn off the voice alert . Identify voice alert that cannot be turned off.	
39.	Locate the help screens and service wrench on the GCI [®] Touchscreen.	

Hill-Rom reserves the right to make changes without notice in design, specifications and models. The only warranty Hill-Rom makes is the express written warranty extended on the sale or rental of its products.

©2017 Hill-Rom Services, Inc. ALL RIGHTS RESERVED. 203848 rev 1 03-AUG-2017 ENG – US

